imagePROGRAF TA-20 **COMPACT AND INTUITIVE DEVICE FOR HIGH PRINT QUALITY**

A versatile and compact multi-purpose printer designed for schools, offices and retail with low volume print jobs.







- High Print Quality Innovative imaging technology delivers precise printing, with powerful colour from LUCIA TD ink
- Quiet and compact Seamlessly fits into any office, with reduced operation noise and full front accessibility
- Accurate ink placement
 Drint sharp lines with an inpervat

Print sharp lines with an innovative Air Feeding System that keeps paper flat for high accuracy

Strengthened security

Security requirements and settings for secure communication, secure management and secure interface

Ease of use

3" inch color LCD touchscreen panel with ample icons for immediate access



PRODUCT RANGE

imagePROGRAF TA-30



imagePROGRAF TA-20



imagePROGRAF TM-200



TECHNICAL SPECIFICATIONS

imagePROGRAF **TA-20**

TECHNOLOGY	1		Margins Printable area	Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Printer Type	5 colors 24"/610mm			Roll paper (borderless): Top: 20 mm, Bottom: 0 mm, Side: 0 mm
Print Technology	Canon Bubblejet on Demand 6 colours integrated type			Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm
	(6 chips per print head x 1 print head)		Media Feed Capacity	Manually switchable by user
Print Resolution	2,400 x 1,200 dpi		Media Take-up roll unit	N/A
Number of Nozzles	15,360 nozzles (MBK 5,120 nozzles, Other Colors 2,560 nozzles each)		Borderless Printing Width (Roll Only)	(Printable) 203.2-610mm *Roll paper only * No size restriction
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only		Maximum number of delivered prints DIMENSIONS AND WEIGHT	Standard position: 1 sheet
Nozzle Pitch	1,200dpi (2 lines)		Physical Dimensions WxDxH	982 x 748 x 438 mm
Ink Droplet Size	minimum 5 pl per colour		(mm) and Weight (Kg)	37 kg (including Roll Holder Set, excluding ink and print
Ink Capacity	Sales Ink: 55ml Bundled Starter Ink: 55ml (2 x MBK, 1 x BK,C,M,Y)		Packaged Dimensions WxDxH	head) Printer (Main unit with pallet) 1147 x 874 x 542 mm 49 kg
Ink Type	Pigment inks - Matte Black, Black, Cyan, Magenta, Yellow		(mm) and Weight (Kg)	49 kg
OS Compatability	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10 Microsoft Windows 64 Bit: Windows 7, 8.1, 10, Windows Server 2008R2, Windows Server		POWER AND OPERATING REQUIREMENTS	
	2012/2012R2, Win	dows Server 2016,	Power Supply	AC 100-240V (50-60Hz)
	Windows Server 2 Apple Macintosh:	2019 OS X 10.10.5~OS X 10.11,	Power Consumption	Operation: 52 W or less
Printer Languages	macOS 10.12- macOS 10.15 SG Raster (Swift Graphic Raster),HP-GL/2, HP RTL, JPEG (Ver. JFIF1.02)			Sleep mode: 3.6W or less Default setting for the time to enter the Sleep mode: approx. 5 mins Power off: 0.3 W or less
Standard Interfaces	USB B Port: Hi-Speed Ethernet: IEEE 802.3 10base-T/IEEE 802.3u 100base-TX/ IEEE 802.3ab 1000base-T/IEEE 802.3x Full Duplex Wireless LAN: IEEE802.1in/IEEE802.1ig/IEEE802.1ib * Please refer to user manual how to activate /deactivate the wireless LAN		Operating Environment	Temperature: 15~30°C, Humidity: 10-80% RH (no dew condensation)
			Accoustic Noise (Power/Pressure)	Operation: 42 dB (A) (Plain paper, line drawing, standard mode) Standby: 35 dB (A) or less Operation: 5.8 Bels (Plain paper, line drawing, standard or db) (Moseured ex 160 7370 et and decembed
MEMORY				mode) (Measured on ISO 7779 standard and described based on ISO9296 standard)
Standard memory	2 GB		Regulations	Europe: CE mark, Russia: EAC,
Hard Drive	NO		Certificates	TUV, CB
PRINT TIME FOR A1 PAGE				
SIZE			WHAT'S INCLUDED	
Media Type			What's in the Box?	Printer, 1 print head, Power Cabel, 1 set of starter ink tanks, Set up guide, Quick Guide, Safety/Standard
CAD Drawing	Print Mode	Print Time		Environment leaflet, User Software CD-ROM (Win),
Plain Paper (A1 size Portrait)	Fast Standard	00:32 min 00:56 min		EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet
Poster	Print Mode	Print Time	Software Included	imagePROGRAF TA- Unified Printer Driver,
Plain Paper (A1 size Portrait)	Fast Standard	00:30 min 00:49 min		Other software available as Download from Web.
Heavy Coated Paper	Print Mode	Print Time	OPTIONS	
(A1 paper size)	Fast Standard	00:58 min 01:46 min	Optional Items	2/3" Roll Holder: RH2-28
			CONSUMABLES	
MEDIA HANDLING	Feed and Output Roll Paper: One Roll, Upper-loading, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)		User Replaceable Items	Ink Tank: PFI-030 (55ml)
Media Feed and Output				Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31
Media Width	Roll paper: 203.2 Cut sheet: 210 - 43			
Media Thickness	Roll/Cut: 0.07 - 0.	8 mm		
Minimum Printable Length	Roll paper: 203.2 r Cut sheet: 279.4 n			
Maximum Printable Length	Roll paper: 18 m (Varies according Cut sheet: 594mm	to the OS and application)	Disclaimer Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ¹⁴ and (B): All company and/or product names are trademarks and/or registered trademarks of their area to the date of the bit bit bit with the set of the area to the set.	
Maximum Media Roll Diameter	150 mm or less			

Maximum Media Roll Diameter Media Core Size Margins Recommended area

Internal diameter of roll core: 2"/3"(option) Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

FINE





PosterArtist Lite

Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2019



Canon recommends you use Caper the Caper to the commends of the commends

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.